

## **BLANK PAGE**



IS 6920: 1993 ISO 1532: 1973

## भारतीय मानक

# मछली पकड़ने के जाल - आकार देने के लिए गांठदार जाल को काटना (टेपरिंग)

(पहला पुनरीक्षण)

Indian Standard

# FISHING NETS — CUTTING KNOTTED NETTING TO SHAPE ('TAPERING')

(First Revision)

UDC 677'076'732/'736: 639'2'081'11: 677'027'613'2

© BIS 1993

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

#### NATIONAL FOREWORD

This Indian Standard which is identical with ISO 1532: 1973 'Fishing nets — Cutting knotted netting to shape ('tapering')' issued by the International Organization for Standardization (ISO), was adopted by the Bureau of Indian Standards on the recommendation of the Textile Materials for Marine/Fishing Purposes Sectional Committee (TX 18) and approval of the Textile Division Council.

In this standard certain terminology and conventions are not identical with those used in Indian Standards; attention is particularly drawn to the following:

Wherever the words 'International Standard' appear, referring to this standard, they should be read as 'Indian Standard'.

In this Indian Standard, the following international standards are referred to. Read in their respective place the following:

International Standard

Indian Standard

ISO 1107 Fishing nets — Netting — Basic terms and definitions

IS 4402:1993 Fishing nets — Netting — Basic terms and definitions (Identical)

IS 6920 : 1993

ISO 1532: 1973

### Indian Standard

# FISHING NETS — CUTTING KNOTTED NETTING TO SHAPE ('TAPERING')

(First Revision)

#### 1 SCOPE AND FIELD OF APPLICATION

This International Standard defines the different kinds of cutting knotted netting to shape by straight cut, the types of cutting (N-, T- and Bar-cut) and gives rules for the designation of the cutting rate.

#### 2 REFERENCE

ISO 1107, Fishing nets — Netting — Basic terms and definitions.  $^{1)}$ 

#### 3 TERMINOLOGY

The expression cutting knotted netting to shape is here understood to mean the cutting from knotted netting of pieces in the shape of trapezia, triangles, parallelograms or other polygons.

#### 4 TYPES OF CUTTING

Depending on the desired final shape of the netting, tapering cuts must be made in suitable ways, The various cutting rates are obtained by combining different lengths of cuts, either along a row of sequential knots (N- or T-cuts respectively) or parallel to a line of sequential mesh bars (B-cuts). See ISO 1107.

The cuts along a row of sequential knots are distinguished by their situation in the drawing of the net or in the netting that has been hung up for tapering as described in 4.1.1 and 4.1.2.

4.1 K-cuts (knot cuts): Cuts just beyond the knots.

Symbol K

NOTE — The term "K-cut" may be used instead of the two following terms in cases where the relation to the general course of the netting yarn is insignificant.

**4.1.1** *N-cut* (vertical cut) : A cut at right angles to the general course of the netting yarn just beyond the knots.

Symbol N




FIGURE 1

**4.1.2** *T-cut* (horizontal cut) : A cut parallel to the general course of the netting yarn just beyond the knots.

Symbol T




FIGURE 2

<sup>1)</sup> At present at the stage of draft. (Revision of ISO/R 1107.)

**4.2** Bar-cut: A cut parallel to a line of sequential mesh bars, each from adjacent meshes, and severing one or more bars.

#### Symbol B




FIGURE 3

#### **5 CUTTING RATE**

#### 5.1 Definition of the cutting rate

To obtain a desired shape and area of netting by tapering, N- or T-cuts and B-cuts of a distinct length must follow each other in a rhythmical way. This rhythmical alternation of the various types of cuts is called "cutting rate".

#### 5.2 Designation of the cutting rate

The cutting rate is determined by the lengths of consecutive sections of N- or T-cuts and B-cuts.

The lengths of the various cuts are indicated

- for the N- and T-cuts by the number of consecutive meshes cut;
- for the B-cut by the number of consecutive bars severed along the cutting edge, not counting the bars on the preceding knot.

To describe the cutting rate for tapering netting, the number and the type of each cut are indicated, giving first N- or T-cuts, then B-cuts.

The following combinations are used for cutting netting to shape:

N- and B-cuts

T- and B-cuts

N- and T-cuts

Exceptions are cutting rates where any of the named types of cutting is used alone. For these the following symbols are valid:

AB = all bars cut

AN = all cuts entirely in N-direction
(at right angles to the general course of the netting yarn)

AT = all cuts entirely in T-direction (parallel to the general course of the netting yarn)

#### 5.3 Examples of the designation of the cutting rate

**5.3.1** Example: 1N2B means the rhythmical alternation of one N-cut and two B-cuts.




FIGURE 4

**5.3.2** Example: 1T2B means the rhythmical alternation of one T-cut and two B-cuts.




FIGURE 5

5.3.3 Example: 1N2T means the rhythmical alternation of one N-cut and two T-cuts.




FIGURE 6

NOTE - Examples of tapering are given in the Annex.

IS 6920 : 1993


ISO 1532 : 1973

#### 6 VARIOUS KINDS OF CUTTING (TAPERING)

**6.1** By tapering only one edge of the netting, right-angled trapezia or right-angled triangles are made.




**6.2** By using the same cutting rate in the same direction on two opposite edges of the netting, parallelograms are made.



In the case of netting in the shape of a parallelogram, the triangular piece cut off on one side may be joined to the other edge (see Figure 10).


## 6.3 Netting in the shape of isosceles trapezia or isosceles triangles



The area of such netting may be divided into two right-angled trapezia or triangles respectively, each of these parts being tapered correspondingly in opposite directions.

For triangular shaped netting (see Figure 12) each of the two halves must be tapered to a point.

#### 6.4 Netting in the shape of asymmetrical trapezia




The area of such netting may be divided into one right-angled trapezium and one right-angled triangle respectively, each of these parts being tapered correspondingly.

IS 6920 : 1993 ISO 1532 : 1973


ANNEX

### EXAMPLES OF TAPERING



Taper cuts losing meshes in suspended netting. Cutting into the piece — tapered piece on left.

IS 6920 : 1993 ISO 1532 : 1973



Taper cuts gaining meshes in suspended netting.

Cutting away from the piece — tapered piece on left.

#### Standard Mark

The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

#### **Bureau of Indian Standards**

BIS is a statutory institution established under the Bureau of Indian Standards Act, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

#### Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

#### Revision of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Handbook and 'Standards Monthly Additions'. Comments on this Indian Standard may be sent to BIS giving the following reference:

Doc: No. TX 18 (0160)

#### Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected		
_				
	BUREAU OF INDIAN STANDARDS	3		
Headquarters:				
Manak Bhavan, 9 Bahad Telephones: 331 01 31,	lur Shah Zafar Marg, New Delhi 110002 331 13 75	Telegrams: Manaksanstha (Common to all Offices)		
Regional Offices !		Telephone		
Central: Manak Bhavan NEW DELHI	, 9 Bahadur Shah Zafar Marg 110002	{331 01 31 {331 13 75		
Eastern: 1/14 C. I. T. S. CALCUTTA	cheme VII M, V. I. P. Road, Maniktola /	<b>37</b> 84 99, 37 85 61 <b>37</b> 86 26, 37 86 62		
Northern: SCO 445-446,	Sector 35-C, CHANDIGARH 160036	\$53 38 43, 53 16 40 \$53 23 84		
Southern: C. I. T. Camp	pus, IV Cross Road, MADRAS 600113	{235 02 16, 235 04 42 235 15 19, 235 23 15		
Western: Manakalaya, BOMBAY 40	E9 MIDC, Marol, Andheri (East) 0093	632 92 95, 632 78 58 632 78 91, 632 78 92		
Branches: AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR. LUCKNOW. PATNA. THIRUVANANTHAPURAM.				